

Geo-Fix[®]

All Weather

- Can be used in virtually all weather conditions
- Even apply in the wet
- Simply brush into joints and compact
- Ready to use – no mixing
- Cement free – no staining
- Sets hard – won't crack or wash out
- Resists weed and plant growth
- For all joints of 6mm wide and over
- Water permeable, allows water to escape

Geo-Fix[®]

All Weather



Geo-Fix[®]

All Weather

THE JOINTING COMPOUND YOU
REALLY CAN

Use in the wet!



**USE ON
PAVING,
SLABS,
COBBLES &
STONE SETTS**

Coverage Calculator

Paving Size/mm	10mm Joint Width, 25mm Depth/ M ²
600 X 600	8.25 - 9.0
600 X 450	6.50 - 7.25
450 X 450	5.75 - 6.25
300 X 450	4.75 - 5.25
300 X 300	3.75 - 4.25

The above figures show the coverage for a 14kg pack being used.



Everbuild Building Products Ltd

Site 41, Knowsthorpe Way,
Cross Green Industrial Estate
Leeds LS9 0SW

Telephone: 0113 240 3456

Fax: 0113 240 0024

Email: info@everbuild.co.uk

Websites: www.everbuild.co.uk

www.geo-fix.co.uk

Everbuild Ireland

Unit 4A, South City Business Park
Tallaght, Dublin 24

Telephone: 01 451 0700

Fax: 01 451 1600

Email: info@everbuild.eu

Website: www.everbuild.eu



Geo-Fix[®] All Weather

Reigns WHEN IT POURS

As the undisputed ruler of the market, Geo-fix is already the trade's favourite paving jointing compound.

Now, new breakthrough formula Geo-fix All Weather solves the perennial problem of applying in wet weather.

Easier & Faster

Geo-Fix All Weather is ready mixed and can simply be brushed into joints with minimal effort compared to using traditional mortar.

Geo-Fix All Weather can be applied in any weather conditions – even while it's raining!

Geo-Fix All Weather is easily finished by compacting with a pointing tool and used on joint widths of min 6mm and a minimum of 25mm deep.

Geo-Fix All Weather forms a solid joint that resists weed and plant growth, yet is permeable allowing water to escape to prevent ponding.

Available in 14kg packs in **Natural Stone, Slate Grey and Anthracite.**



The colours shown are as accurate as the limitations of the printing process allow. Please refer to actual product samples before purchasing.



How to use Geo-Fix[®]



Step 1
Wet entire area to be jointed. Use a hosepipe with a hose nozzle or a watering can with rose.



Step 2
Sweep off the excess pools of standing water.



Step 3
Carefully open the vacuum-packed bag and sprinkle Geo-Fix All Weather Jointing Compound over the area to be jointed.



Step 4
Using a soft brush, push the Geo-Fix All Weather Jointing Compound into the joints at 45° angle.



Step 5
Firmly compact the Geo-Fix All Weather Jointing Compound with a pointing tool, refill and repeat ensuring a fully compacted and topped up joint.



Step 6
Finish the surface decoratively giving a smooth, flat finish with a pointing tool then move onto the next area. Firm compaction is the key to the successful laying of Geo-Fix All Weather Jointing Compound.



Step 7
After application brush off excess with a soft brush, taking care not to brush out any Geo-Fix All Weather Jointing Compound from treated joints. Once cured, sit back and enjoy your new patio.

**EVEN
APPLY IN
THE WET!**

