

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 3011 Osmo Polyx®-Oil Original

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the preparation

Paint
 Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf

Further information obtainable from:

Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

Classification according to

Directive 67/548/EEC or Directive 1999/45/EC

Not applicable.

Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists and extended by company and literature data.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008

Void

Hazard pictograms

Void

Signal word

Void

Hazard statements

Void

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

Trade name: 3011 Osmo Polyx®-Oil Original

(Contd. of page 1)

P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.



Contains 2-butanonoxime. May produce an allergic reaction.

Safety data sheet available on request.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	30-60%
Index number: 649-327-00-6	 Xn R65	
Reg.nr.: 01-2119457273-39	R66	
	 Asp. Tox. 1, H304	

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:** Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

Dizziness

Headache

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

Trade name: 3011 Osmo Polyx®-Oil Original

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.

Use only in well ventilated areas.
Keep receptacles tightly sealed.
Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

Trade name: 3011 Osmo Polyx®-Oil Original

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:**

Store only in the original receptacle.
Store in a cool location.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Keep container tightly sealed.

Storage class:

10

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about**design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****64742-48-9 aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m ³ , 150 ppm ppm Source: UK SIA
-----------	--

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Not necessary if room is well-ventilated.
Use suitable respiratory protective device only when aerosol or mist is formed.
Short term filter device:
Filter A/P2

Protection of hands:

Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
To avoid skin problems reduce the wearing of gloves to the required minimum.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

Trade name: 3011 Osmo Polyx®-Oil Original

(Contd. of page 4)

Material of gloves	Nitrile rubber, NBR
Penetration time of glove material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the permanent contact gloves made of the following materials are suitable:	Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).
For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:	Nitrile rubber, NBR
Eye protection:	If risk of splashing: Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side protection)
Body protection:	Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Viscous
Colour:	Yellowish
Odour:	Mild

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	180 °C

Flash point: >63 °C (DIN 53213)

Ignition temperature: 240 °C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:	0.7 Vol %
Upper:	6.0 Vol %

Density at 20 °C: 0.80-0.95 g/cm³ (DIN 51757)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

Trade name: 3011 Osmo Polyx[®]-Oil Original

(Contd. of page 5)

Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Viscosity: Kinematic at 20 °C:	25-35 s (DIN 53211/4mm)
Solvent content: VOC (EC)	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects**Acute toxicity:****LD/LC50 values relevant for classification:****64742-48-9 aliphatic hydrocarbons, C10-C13**

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	> 5 mg/l (rat) (OECD 403)

96-29-7 2-butanonoxime

Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50 / 4h	>10.5 mg/l (rat)

(Contd. on page 7)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

Trade name: 3011 Osmo Polyx®-Oil Original

(Contd. of page 6)

Primary irritant effect:**on the skin:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye:

Irritating effect.

Sensitization:

Sensitizing effect by skin contact is possible by prolonged exposure.

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

Sensitisation

Contains 2-butanonoxime. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h > 1000 mg/l (daphnia) (OECD 202)

EC50/ 72h > 1000 mg/l (algae) (OECD 201)

LC50 / 96h > 1000 mg/l (fish) (OECD 203)

96-29-7 2-butanonoxime

EC50 / 48h 201 mg/l (daphnia)

IC50 / 72h 11.8 mg/l (algae)

LC50 / 96h >100 mg/l (fish)

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

Trade name: 3011 Osmo Polyx®-Oil Original

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10*	packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation":

-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

GISBAU-Code

GISCODE: Ö60

VOC (EC)

< 500 g/l (VOC-max. = 500 g/l (2010 A/i))

(Contd. on page 9)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 06.01.2014

Version number 1

Revision: 06.01.2014

Trade name: 3011 Osmo Polyx®-Oil Original

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H304 May be fatal if swallowed and enters airways.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Department issuing MSDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the

preparation

Paint

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12

D-48231 Warendorf

Further information obtainable

from:

Product safety department

Phone: +49 (0) 251 / 692 - 188

Fax: +49 (0) 251 / 692 - 462

e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Directive 67/548/EEC or Directive

1999/45/EC

Not applicable.

Information concerning

particular hazards for human and

environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists and extended by company and literature data.

2.2 Label elements

Labelling according to EU

guidelines:

The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

Safety phrases:

2 Keep out of the reach of children.

24/25 Avoid contact with skin and eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

46 If swallowed, seek medical advice immediately and show this container or label.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

(Contd. of page 1)

51 Use only in well-ventilated areas.

Special labelling of certain preparations:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Contains 2-butanonoxime. May produce an allergic reaction.

Safety data sheet available for professional user on request.

Additional information:

Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

3 Composition/information on ingredients

3.2 Chemical characterization: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25-50%
EC number: 918-481-9	Xn R65	
Index number: 649-327-00-6	R66	
Reg.nr.: 01-2119457273-39	Acute Tox. 3, H331; Asp. Tox. 1, H304	

Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures**General information:**

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

In case of unconsciousness place patient stably in side position for transportation.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness

Headache

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Keep receptacles tightly sealed.
Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:**

Store only in the original receptacle.
Store in a cool location.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Keep container tightly sealed.

7.3 Specific end use(s)

No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Not necessary if room is well-ventilated.
Use suitable respiratory protective device only when aerosol or mist is formed.
Short term filter device:
Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 ° C)).

Protection of hands:

Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves

Nitrile rubber, NBR

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

(Contd. of page 4)

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Goggles recommended during refilling

Body protection:

Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Viscous**Colour:** According to product specification**Odour:** Mild

Change in condition

Melting point/Melting range: Undetermined.**Boiling point/Boiling range:** 180°C**Flash point:** >63°C (DIN 53213)**Ignition temperature:** 240°C**Self-igniting:** Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 0.7 Vol %**Upper:** 6.0 Vol %**Density at 20°C:** 0.88-0.90 g/cm³ (DIN 51757)

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Viscosity:

Kinematic at 20°C: 25-35 s (DIN 53211/4mm)

Solvent content:

VOC (EC) < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

(Contd. of page 5)

9.2 Other information

No further relevant information available.

10 Stability and reactivity**10.1 Reactivity****10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

11 Toxicological information**11.1 Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****64742-48-9 aliphatic hydrocarbons, C10-C13**

Oral LD50 > 5000 mg/kg (rat) (OECD 401)

Dermal LD50 > 5000 mg/kg (rat) (OECD 402)

Inhalative LC50 / 4h > 5 mg/l (rat) (OECD 403)

96-29-7 2-butanonoxime

Oral LD50 3700 mg/kg (rat)

Dermal LD50 200-2000 mg/kg (rat)

Inhalative LC50 / 4h >10.5 mg/l (rat)

Primary irritant effect:**on the skin:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye:

Irritating effect.

Sensitization:

Sensitizing effect by skin contact is possible by prolonged exposure.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

(Contd. of page 6)

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

12 Ecological information

12.1 Toxicity

Aquatic toxicity:

64742-48-9 aliphatic hydrocarbons, C10-C13

EC50 / 48h > 1000 mg/l (daphnia) (OECD 202)

EC50/ 72h > 1000 mg/l (algae) (OECD 201)

LC50 / 96h > 1000 mg/l (fish) (OECD 203)

96-29-7 2-butanonoxime

EC50 / 48h 201 mg/l (daphnia)

IC50 / 72h 11.8 mg/l (algae)

LC50 / 96h >100 mg/l (fish)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 10* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

(Contd. of page 7)

Recommended cleansing agents: Solvent naphtha

14 Transport information

14.1 UN-Number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

GISBAU-Code GISCODE: Ö60
VOC (EC) < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H304 May be fatal if swallowed and enters airways.
H331 Toxic if inhaled.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.

Department issuing MSDS: product safety department
Contact: Hr. Dr. Starp

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.07.2012

Version number 13

Revision: 02.07.2012

Trade name: 3032 Osmo Polyx Hardwax-Oil Original, clear satin

(Contd. of page 8)

**** Data compared to the previous
version altered.***

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 4

Revision: 17.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 3065 Osmo Polyx Hardwax-Oil Original, semi-matt

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the preparation

Paint
Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf

Further information obtainable from:

Product safety department
Phone: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

Classification according to

Directive 67/548/EEC or Directive 1999/45/EC

Not applicable.

Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists and extended by company and literature data.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Precautionary statements Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

(Contd. on page 2)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 4

Revision: 17.01.2014

Trade name: 3065 Osmo Polyx Hardwax-Oil Original, semi-matt

(Contd. of page 1)



P102 Keep out of reach of children.
 P101 If medical advice is needed, have product container or label at hand.
 P262 Do not get in eyes, on skin, or on clothing.
 P271 Use only outdoors or in a well-ventilated area.
 P501 Dispose of contents/container in accordance with local/regional/national/
 international regulations.

Additional information: Observe the general safety regulations when handling chemicals.
 Always wear a dust mask when sanding.
 Contains 2-butanonoxime. May produce an allergic reaction.
 Safety data sheet available on request.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25-50%
Index number: 649-327-00-6	 Xn R65	
Reg.nr.: 01-2119457273-39	R66	
	 Asp. Tox. 1, H304	

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:** Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

Dizziness

Headache

(Contd. on page 3)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 4

Revision: 17.01.2014

Trade name: 3065 Osmo Polyx Hardwax-Oil Original, semi-matt

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
 Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.
 Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.
 Use only in well ventilated areas.
 Keep receptacles tightly sealed.
 Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 4

Revision: 17.01.2014

Trade name: 3065 Osmo Polyx Hardwax-Oil Original, semi-matt

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:**

Store only in the original receptacle.
Store in a cool location.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Keep container tightly sealed.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about**design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****64742-48-9 aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m ³ , 150 ppm ppm
	Source: UK SIA

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Not necessary if room is well-ventilated.
Use suitable respiratory protective device only when aerosol or mist is formed.
Short term filter device:

Filter A/P2

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves

Nitrile rubber, NBR

(Contd. on page 5)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 4

Revision: 17.01.2014

Trade name: 3065 Osmo Polyx Hardwax-Oil Original, semi-matt

(Contd. of page 4)

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

If risk of splashing:

Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side protection)

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Viscous

Colour: According to product specification

Odour: Mild

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 180 °C

Flash point: >61 °C (DIN EN ISO 2719)

Ignition temperature: 240 °C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 0.7 Vol %

Upper: 6.0 Vol %

Density at 20 °C: 0.915-0.925 g/cm³ (DIN 51757)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 4

Revision: 17.01.2014

Trade name: 3065 Osmo Polyx Hardwax-Oil Original, semi-matt

(Contd. of page 5)

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Viscosity:

Dynamic at 20 °C: 115 -135 mPas

Kinematic at 20 °C: > 30 s (ISO 2431/3mm)

Solvent content:

VOC (EC) < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	> 5 mg/l (rat) (OECD 403)

96-29-7 2-butanonoxime

Oral	LD50	3700 mg/kg (rat)
------	------	------------------

(Contd. on page 7)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 4

Revision: 17.01.2014

Trade name: 3065 Osmo Polyx Hardwax-Oil Original, semi-matt

(Contd. of page 6)

Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50 / 4h	>10.5 mg/l (rat)

Primary irritant effect:**on the skin:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye:

Irritating effect.

Sensitization:

Sensitizing effect by skin contact is possible by prolonged exposure.

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)

96-29-7 2-butanonoxime

EC50 / 48h	201 mg/l (daphnia)
IC50 / 72h	11.8 mg/l (algae)
LC50 / 96h	>100 mg/l (fish)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 4

Revision: 17.01.2014

Trade name: 3065 Osmo Polyx Hardwax-Oil Original, semi-matt

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H304 May be fatal if swallowed and enters airways.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Department issuing MSDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

*** Data compared to the previous version altered.**

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the preparation

Paint
Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf

Further information obtainable from:

Product safety department
Phone: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

Classification according to

Directive 67/548/EEC or Directive 1999/45/EC

Not applicable.

Information concerning

particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists and extended by company and literature data.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Precautionary statements Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 1)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P262 Do not get in eyes, on skin, or on clothing.
 P271 Use only outdoors or in a well-ventilated area.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.



Additional information:

Observe the general safety regulations when handling chemicals.
 Always wear a dust mask when sanding.
 Contains 2-butanonoxime. May produce an allergic reaction.
 Safety data sheet available on request.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25-50%
Index number: 649-327-00-6	 Xn R65	
Reg.nr.: 01-2119457273-39	R66	
	 Asp. Tox. 1, H304	

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:**

Take affected persons out into the fresh air.
 Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

In case of unconsciousness place patient stably in side position for transportation.
 Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness
 Headache

(Contd. on page 3)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
 Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.
 Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.
 Use only in well ventilated areas.
 Keep receptacles tightly sealed.
 Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:**

Store only in the original receptacle.
Store in a cool location.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Keep container tightly sealed.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about**design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****64742-48-9 aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m ³ , 150 ppm ppm
	Source: UK SIA

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Not necessary if room is well-ventilated.
Use suitable respiratory protective device only when aerosol or mist is formed.
Short term filter device:

Filter A/P2

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves

Nitrile rubber, NBR

(Contd. on page 5)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 4)

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

If risk of splashing:

Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side protection)

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Viscous

Colour: Yellowish

Odour: Mild

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: > 180 °C

Flash point: > 63 °C (DIN EN ISO 2719)

Ignition temperature: 240 °C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 0.7 Vol %

Upper: 6.0 Vol %

Density at 20 °C: 0.92-0.95 g/cm³

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 5)

Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Viscosity:	
Dynamic at 20 °C:	150-180 mPas
Kinematic at 20 °C:	25-35 s (DIN 53211/4mm)
Solvent content:	
VOC (EC)	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	> 5 mg/l (rat) (OECD 403)

96-29-7 2-butanonoxime

Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 6)

Inhalative	LC50 / 4h	>10.5 mg/l (rat)
------------	-----------	------------------

Primary irritant effect:**on the skin:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye:

Irritating effect.

Sensitization:

Sensitizing effect by skin contact is possible by prolonged exposure.

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

Sensitisation

Contains 2-butanonoxime. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)

96-29-7 2-butanonoxime

EC50 / 48h	201 mg/l (daphnia)
IC50 / 72h	11.8 mg/l (algae)
LC50 / 96h	>100 mg/l (fish)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10	packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation":

-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

GISBAU-Code

GISCODE: Ö60

VOC (EC)

< 500 g/l (VOC-max. = 500 g/l (2010 A/i))

(Contd. on page 9)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H304 May be fatal if swallowed and enters airways.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Department issuing MSDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

*** Data compared to the previous version altered.**